



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/033,549	12/27/2001	Pavel G. Polynkin	2102393-991130	7501

7590

03/05/2003

David L. Alberti
Gray Cary Ware & Freidenrich
1755 Embarcadero Road
Palo Alto, CA 94303

EXAMINER

STAHL, MICHAEL J

ART UNIT

PAPER NUMBER

2874

DATE MAILED: 03/05/2003

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

10/033,549

Applicant(s)

POLYNKIN ET AL.

Examiner

Mike Stahl

Art Unit

2874

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☐ Responsive to communication(s) filed on ____.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-38 is/are pending in the application.
- 4a) Of the above claim(s) ____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) ____ is/are allowed.
- 6) ☒ Claim(s) 1-38 is/are rejected.
- 7) ☐ Claim(s) ____ is/are objected to.
- 8) ☐ Claim(s) ____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 27 December 2001 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
- Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- 11) ☐ The proposed drawing correction filed on ____ is: a) ☐ approved b) ☐ disapproved by the Examiner.
- If approved, corrected drawings are required in reply to this Office action.
- 12) ☒ The oath or declaration is objected to by the Examiner.

Priority under 35 U.S.C. §§ 119 and 120

- 13) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. ____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.
- 14) ☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 119(e) (to a provisional application).
- a) ☐ The translation of the foreign language provisional application has been received.
- 15) ☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. §§ 120 and/or 121.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO-1449) Paper No(s) ____.
- 4) ☐ Interview Summary (PTO-413) Paper No(s). ____.
- 5) ☐ Notice of Informal Patent Application (PTO-152)
- 6) ☐ Other: _____.

Oath/Declaration

The oath or declaration is defective. A new oath or declaration in compliance with 37 CFR 1.67(a) identifying this application by application number and filing date is required. See MPEP §§ 602.01 and 602.02.

The oath or declaration is defective because:

It does not identify the mailing or post office address of each inventor. A mailing or post office address is an address at which an inventor customarily receives his or her mail and may be either a home or business address. The mailing or post office address should include the ZIP Code designation. The mailing or post office address may be provided in an application data sheet or a supplemental oath or declaration. See 37 CFR 1.63(c) and 37 CFR 1.76.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 1-4, 7-11, and 32-35 are rejected under 35 U.S.C. 102(b) as being anticipated by Solgaard et al. (US 6097859).

Solgaard discloses an apparatus (fig. 8) comprising an input port (which includes fiber 68), a wavelength disperser 70, an array 74 of beam-manipulating elements positioned to correspond with the dispersed channels, and an optical detector 78. The beam-manipulating elements are operable in a time-division-multiplexed manner (col. 9 lines 10-12 and 21-27). The apparatus thus satisfies claim 1, and the method of using it satisfies claim 32.

As to claims 2-4 and 35, the beam-manipulating elements are micromirrors, are fabricated from silicon, and are pivotable about at least one axis (additional details of the

Art Unit: 2874

micromirrors are shown in figs. 2 and 3 and are described at col. 4 lines 28-36 and col. 6 line 57 – col. 7 line 49).

As to claim 7, the disperser **70** is a diffraction grating.

As to claim 8, the detector **78** is referred to as a photodiode detector, so it is believed to be either a PN or PIN type device.

As to claim 9, the input port includes a fiber collimator (see element **26** in fig. 1) and a fiber **68**. As to claim 10, the fiber is a single mode fiber (Table 1).

The apparatus includes a beam-focuser **72** for focusing the spectral channels onto corresponding spots on the beam-manipulating elements, as required by claim 11.

As to claim 33, the spectral channels may be directed into the detector sequentially (col. 9 lines 9-12). As to claim 34, it is asserted that it is within the scope of Solgaard to send a selected grouping of spectral channels to the detector simultaneously, even though “normal” operation involves only one channel at a time (col. 9 lines 26-27).

Claims 1-7, and 32-35 are rejected under 35 U.S.C. 102(b) as being anticipated by Stafford (US 5504575).

Stafford discloses an apparatus (fig. 3) including an input port (e.g. via slit **60**), a wavelength-disperser **80** that splits the input signal into a number of spectral channels, an array of beam-manipulating elements **93** positioned to correspond to the channels, and a detector **100**. The beam-manipulating elements are individually controllable and can direct the channels into the detector in a time-division-multiplexed sequence (col. 4 lines 39-44). The Stafford apparatus therefore satisfies claim 1, and the method of using it satisfies claims 32 and 33.

Art Unit: 2874

As to claims 2, 4, and 35, in one embodiment the beam-manipulating elements 93 are rotatable micromirrors (col. 3 line 67 – col. 4 line 15; claims 1 and 6). As to claim 3, the micromirror devices (DMDs) used by Stafford and disclosed in Hornbeck (US 5061049) are micromachined silicon mirrors.

As to claim 5, the micromirrors are used as shutters. As to claim 6, the shutters may alternatively be liquid crystal shutter elements (col. 4 lines 46-49; claims 1 and 7).

Regarding claim 7, the dispersing element 80 is a prism in the exemplary embodiment, but may alternatively be a transmission grating (col. 3 lines 61-63).

As to claim 34, the spectral channels passed to the detector may be grouped arbitrarily. Stafford describes a specific example of channel groupings at col. 6 line 62 – col. 7 line 3).

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claims 18-21, 24-31, and 36-38 are rejected under 35 U.S.C. 103(a) as being unpatentable over Solgaard et al. in view of Braun et al. (US 6177992).

Solgaard discloses all the features of claims 18 and 36 except for a polarization separator and a polarization rotator. The input optical signals in Solgaard appear to be limited to a single polarization, and the only treatment pertaining thereto is the inclusion of quarter wave plates to

Art Unit: 2874

compensate for the polarization sensitivity of the gratings. Solgaard does not specifically discuss handling input signals of more than one polarization. However, optical communication systems using orthogonal polarizations are already known in the art.

Braun discloses an arrangement for handling input signals having orthogonal polarizations. The arrangement includes a polarization separator **12** to split an input signal **11** into first and second polarization components, and a polarization rotator **14** to rotate the second component by 90 degrees (fig. 1). The purpose of the arrangement is to change one of the polarization components so that both components are compatible with the grating **16** (col. 1 lines 46-50). Braun also notes that the arrangement is useful for spectral monitoring applications (col. 2 lines 1-5; col. 3 lines 18-22; col. 4 lines 16-19).

Thus Braun teaches a way to overcome a limitation that is present in the Solgaard system, namely, the polarization sensitivity of the grating **70**. It would have been obvious to a person having ordinary skill in the art to apply the polarization separator and rotator taught by Braun to the Solgaard arrangement in order to enable the use of two polarizations, which would in turn beneficially increase the signal handling capacity of the Solgaard system. The proposed combination satisfies claim 18, and the method of using it satisfies claim 36.

Claims 19-21, 26-29, and 31 are satisfied by the Solgaard device alone as described above, and would still be satisfied under the proposed combination.

As to claim 24, the polarization separator **12** taught by Braun is a polarization beam splitter (col. 2 lines 8-13). As to claim 25, the polarization rotator **14** may be a half wave plate (claim 6).

As to claim 37, in the proposed combination there is only a single detector **78**, so that detector would receive both polarizations of a given wavelength.

As to claims 30 and 38, it would have been obvious to a skilled worker to include an additional detector in the proposed combination, so that the polarization components could be separately monitored. It is well known that certain elements of optical fiber communication systems affect different polarization components in differing magnitudes, and accordingly it would be useful to track the effects on each polarization component individually.

Claims 12-17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Solgaard et al. in view of Saunderson (US 3090278).

As to claim 12, Solgaard does not disclose a reference signal and a reference position-sensing element. However, it is well known that gratings such as the grating **70** in Solgaard need to be precisely aligned for proper operation and that ambient conditions (e.g. temperature changes) can cause misalignment. Solgaard does not provide any means for correcting and maintaining the alignment of grating **70**.

Saunderson discloses a spectrometer system. In the fig. 2 embodiment, a reference signal ("monitor radiation") of a particular wavelength is applied to the input port along with other wavelength signals (see also claim 1). The reference signal is diffracted from the grating **28** and propagates to a position-sensing element which includes elements **94-110**. The photomultiplier tubes **102** and **104** generate drive signals for a servo motor **48** that controls the alignment of the grating (fig. 1). The drive signals are representative of the grating position as described at col. 3 lines 29-51.

The overall alignment technique taught by Saunderson is clearly applicable to the spectrometer disclosed in fig. 8 of Solgaard. It would have been obvious to a skilled person to modify the Solgaard arrangement as suggested by Saunderson by providing a reference wavelength signal, a position detector for that signal, and a servo device responsive to the position detector for controlling the position of grating 70 in order to maintain correct alignment of the grating with respect to the other components of the arrangement. The proposed modification would have satisfied the requirements of claims 12, 13, 15, and 17.

As to claim 14, in the proposed modification the arrangement would inherently include an optical combiner since there must be some way of getting the reference wavelength signal into the input fiber 68.

As to claim 16, since the reference wavelength signal would be diffracted from grating 70 along with all the other input wavelength signals, and since the other signals are already incident on the beam-manipulating elements 74, it would have been obvious to a skilled person to locate the position-sensing element with the beam-manipulating elements 74 for simplicity. It is noted that Saunderson places the position-sensing elements in the same array as the exit slits (such as 34 in fig. 1), and the exit slits essentially correspond to the beam-manipulating elements 74 of Solgaard. Moreover, although Saunderson teaches adjustment of the grating position, a skilled person would have understood that the grating could be fixed while the slit / PMT array is moved. Thus in the combination proposed above it would have been obvious to such a person to fix the grating position while rotating the element array 74. One motivation for this alternative arrangement is that the array 74 is larger than the grating and would be more susceptible to misalignments resulting from temperature changes.

Art Unit: 2874

Claims 18-27, 29 and 36 are rejected under 35 U.S.C. 103(a) as being unpatentable over Stafford in view of Braun et al.

Stafford does not describe a beam focuser that focuses the dispersed channels onto the corresponding beam-manipulating elements 93. However, it would have been obvious to a person having ordinary skill in the art to provide lenses to focus the respective channels onto the input end of the corresponding fibers 92 (which ultimately conducts the associated channel to its beam-manipulating element) since it is well known that the transmission efficiency of an optical fiber is extremely sensitive to misalignment, and since the core diameter of an optical fiber is usually much smaller than the outer diameter of the fiber. It would be especially important to maximize the power coupled into the fiber for each channel when the device is used to measure the relative intensity of the channels. Furthermore, the use of lenses to couple light into optical fibers is routine in the art.

Stafford also does not disclose a polarization separator or rotator as required by claims 18 and 36. Braun discloses a general technique for handling signals with orthogonal polarizations as described above. It is noted that while a prism may not be as polarization-sensitive as a grating, it would still be important to have the polarization components properly aligned when passing through LCD shutters, which are used in an alternative embodiment of Stafford and which are typically polarization-sensitive. In another alternative embodiment, a grating may be used instead of the prism as noted above. Therefore the technique taught by Braun would be useful in achieving proper orientation of the polarization components of an input signal in the Stafford device. Accordingly it would have been obvious to a skilled person to provide a polarization splitter, a polarization rotator, and an additional spatial light modulator array 90 in

Art Unit: 2874

the Stafford device in order to enable the handling of signals with orthogonal polarizations. The proposed modification and its method of use would have met the limitations of claims 18-27, 29 and 36.

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

Conclusion


The references made of record and not relied upon is considered pertinent to applicant's disclosure. US 6046808 describes a spectrometer using a grating and a micromirror array. US 6222954 discloses a wavelength division multiplexed cross-connect switch. US 6249346 discloses a monolithically fabricated spectrometer. US 6263123 discloses a spectral analyzer (fig. 4) which has a grating and a micromirror array and which operates in a manner similar to that of the Solgaard device described above. US 6507685 has inventors in common with the present application and describes details of an alignment system which is similar to the one presently disclosed.

Art Unit: 2874

Any inquiry concerning this communication should be directed to Mike Stahl at (703) 305-1520. Official communications eligible for submission by facsimile may be faxed to (703) 308-7724 or (703) 308-7722. Inquiries of a general or clerical nature (e.g., a request for a missing form or paper, etc.) should be directed to the Technology Center 2800 receptionist at (703) 308-0956 or to the technical support staff supervisor at (703) 308-3072.

Michael J. Stahl
Patent Examiner
Art Unit 2874

February 28, 2003


Sup. Supervisory Patent Examiner
Technology Center 2800